

Astro D



Performance


Lumen Output	Wattage	lm/cW
1650lm (4000K)	14.6 W	113.0
2200lm (4000K)	19.6 W	112.2

Rated Supply Voltage	220—240 V
AC Voltage Range	198—264 V
Mains Frequency	50/60 Hz
Output LF Current Ripple @ 120Hz	<1%
Overvoltage Protection	320 V
In-rush Current	2.5 A
THD	<10%
Dimming Type (Optional)	DALI
Operating Temperature	-25 +60 °C
Colour Rendering (3 SDCM)	Ra>82
Longevity (L70/B10)	60,000 hours
IP Rating (when surface mounted)	IP44
Surface Fixing	Ø95mm
Suspended Fixing	2m Suspension Max
Dimensions	Ø195 x 130mm
Weight	2.8 kg
Warranty	5 Years
Certification	CE, ROHS

Emergency (Optional)

BLF	Lumen Output
20%	330lm
15%	330lm

Emergency Duration	3 Hours
Recharge Period	24 Hours
Battery Type	LiFePO4 (Lithium Iron Phosphate)
Battery Pack	3 x 3.2V 1.5Ah
Parasitic Load	1.2W
Operating Temperature	0—60 °C
Power Efficiency	95%
Certification	CE, ROHS



54lighting

Tel: 01202 925971 | Email: info@54lighting.co.uk | Web: www.54lighting.co.uk

54 Lighting, Arrowsmith Court, Station Approach, Poole, Dorset, BH18 8AT