

MELLOW Ø335 & Ø435



Performance

Lumen Output	Wattage	lm/cw
1800lm	14W	128.57
3000lm`	25W	120.00

Rated Supply Voltage	220—240 V
AC Voltage Range	198—264 V
Mains Frequency	50/60 Hz
Output LF Current Ripple @ 120Hz	<5%
Overvoltage Protection	320 V
In-rush Current	5 A
THD	<10%
Dimming Type	DALI2
Operating Temperature	-25... +60 °C
Longevity (L80/B10)	60,000 hours
Colour Rendering (3 SDCM)	Ra>82
IP Rating	IP20
Dimensions	Ø335 x 100mm
Dimensions	Ø435 x 100mm
Weight	1.9 kg 2.3kg
Warranty	5 Years
Certification	CE, ROHS

Emergency Options

BLF	Lumen Output
20%	360lm
15%	450lm

Emergency Type	DALI 2 Monitoring
Emergency Duration	3 Hours
Recharge Period	24 Hours
Battery Type	LiFePO4 (Lithium Iron Phosphate)
Battery Pack	3 x 3.2V 1.5Ah
Parasitic Load	1.2W
Operating Temperature	0—60 °C
Power Efficiency	95%
Certification	CE, ROHS



54 lighting

Tel: 01342 395625 | **Email:** info@54lighting.co.uk | **Web:** www.54lighting.co.uk

Unit 1, Haysbridge Farm, Farm Approach, Brickhouse Lane, South Godstone, Surrey, RH9 8JW